

Product Information: TECNADIS GWR Rain repellent product for vehicles windscreens

DESCRIPTION

- Anti rain composition with high water-repellent properties, facilitating water removal from treated surfaces (Glass)
- Protects the surface against excessive dirt, insects or dust accumulation facilitating its removal from the surface.

BENEFITS

- Suited for the treatment of cars, trucks, buses or trains windscreens.
- Easy to apply
- Good resistance to abrasion (washing systems, wipers, etc). Durability of 12 months / 20.000 Km approximately.
- Avoids the adhesion of ice to the windscreen being easy to remove it from the glass treated.
- Estimated performance: 10-15ml/m²
- It does not release hydrochloric acid when it is applied.

COMPOSITION

- Active agents in a concentration lower than 5% in alcohol base.

APPLICATIONS

- Specially designed for vehicles windscreens; it improves both day and night visibility in rainy situations even allowing not using the windscreen wipers and improving safety when driving under adverse weather conditions.

PHYSICO-CHEMICAL PROPERTIES

- | | |
|----------------------|-----------|
| • Color | Colorless |
| • Active Ingredients | <5% wt. |
| • Solvent | alcohol |
| • Density | 0,80 g/ml |

HOW TO USE

Before the application, the surfaces must be thoroughly cleaned and free from dirt. The use of suitable detergents is recommended. Thoroughly remove rest from cleaners and let dry the surface before product application. The product can be applied directly onto the surface with a spray helping yourself with a microfiber cloth or paper to distribute the product evenly throughout the area. It can also be applied directly to the cloth. Immediately after applying product and using another dry cloth, polish the surface with circular movements to remove the excess of product. The treated surface shows the effect immediately after treatment.

Additional information regarding application and effectiveness:

- Apply with the glass surface completely clean and dry. Avoid conditions of extreme humidity when applying
- It is recommended not to apply the product when the surface is directly exposed to sun or when the surface is too hot (Recommendation: Apply the product at a temperature between 5°C-30°C)
- Consecutive applications give the glass hydrophobic properties of longer durability. It is not necessary to remove the previous treatment.
- It is not necessary to leave a time of drying/curing. The glass can be subjected to the action of the water/rain immediately after the application, although after a timeout of 1-2 hours, the water repellence effect reaches its optimum point.

HANDLING PRECAUTIONS

Product safety information required for safe use is not included in this document. Before handling, read material safety data sheets and container labels for safe use, physical, and health hazard information. The material safety data sheet (MSDS) is available from Tecnan S. L.

USAGE LIFE AN STORAGE

When stored in original sealed containers at temperatures between 5 ° C and 30 ° C, the product lasts for 12 months from the date of manufacture. Avoid direct exposure to sunlight, keep away from heat and flames and prevent it from freezing. The material can settle slowly, therefore it is recommended to shake it before use.

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

Limited warranty information – Please read carefully

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Tecnan's products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent. Tecnan's sole warranty is that the product will meet the Tecnan specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Tecnan specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability. Tecnan disclaims liability for any incidental or consequential damages.